Engineering	
	ACCORD PLUG-IN
Engine Type	In-Line 4-Cylinder
Engine Block/Cylinder Head	Aluminum-Alloy
Displacement (cc)	1993
Horsepower @ rpm (SAE net)	141 @ 6200
Bore and Stroke (mm)	81 x 96.7
Compression Ratio Valve Train	13.0:1
Windows in American Agency and the Control of the C	16-Valve DOHC i-VTEC®
Drive-by-Wire Throttle System	Standard
Eco Assist TM System	Standard
Active Noise Cancellation TM (ANC) Hill Start Assist	Standard Standard
CARB Emissions Rating[1]	SULEV20/TZEV
Direct Ignition System with Immobilizer	Standard
Electric Power Storage	
Liettie I owel Storage	ACCORD BLUC IN
Lithium-Ion Battery	ACCORD PLUG-IN Standard
Volume/Size (kWh)	6.7
Output (Kilowatt/Horsepower)	41 / 55
6.6 kW Onboard 32-Amp Charger	Standard
Approximate Charging Time (hrs, 240V / 120V)[2]	1/3
Electric Motor	
Liectife Motor	A COOPER DE TAGE TO
AC C D	ACCORD PLUG-IN
AC Synchronous Permanent-Magnet Electric Motor Kilowatts (SAE net @ rpm)	Standard 124
	1124
Transmissions	
	ACCORD PLUG-IN
Electronic Continuously Variable Transmission (E-CVT)	Standard
Gear Ratio: 2.450, Final Drive: 3.421	Standard
Body/Suspension/Chassis	
	ACCORD PLUG-IN
Aluminum Hood	Standard
Unit-Body Construction	Standard
MacPherson Strut Front Suspension	Standard
Independent Multi-Link Rear Suspension	Standard
Stabilizer Bar (mm, front/rear)	19 / 16
Electric Power-Assisted Rack-and-Pinion Steering (EPS)	Standard
Steering Wheel Turns, Lock-to-Lock	2.55
Steering Ratio	13.36
Turning Diameter, Curb-to-Curb (ft) Powen Assisted Ventileted Event Diss/Solid Poor Diss Proless (in)	38.1 11.5 / 11.1
Power-Assisted Ventilated Front Disc/Solid Rear Disc Brakes (in) Wheels	17" Forged Alloy with Aero Covers
All-Season Tires	225/50 R17 94V
Tire Repair Kit (TRK) with 24-Hour Assistance	Standard
Exterior Measurements	
	ACCORD PLUG-IN
Wheelbase (in)	109.3
	193.3
Length (in)	
Length (in) Height (in)	57.7
	57.7 72.8
Height (in)	
Height (in) Width (in)	72.8
Height (in) Width (in) Track (in, front/rear)	72.8 62.4 / 62.7
Height (in) Width (in) Track (in, front/rear) Curb Weight (lbs, 6MT/CVT) Weight Distribution (%, front/rear)	72.8 62.4 / 62.7 3799
Height (in) Width (in) Track (in, front/rear) Curb Weight (lbs, 6MT/CVT)	72.8 62.4 / 62.7 3799 56/44
Height (in) Width (in) Track (in, front/rear) Curb Weight (lbs, 6MT/CVT) Weight Distribution (%, front/rear) EPA Mileage Estimates[3] / Fuel	72.8 62.4 / 62.7 3799 56/44 ACCORD PLUG-IN
Height (in) Width (in) Track (in, front/rear) Curb Weight (lbs, 6MT/CVT) Weight Distribution (%, front/rear) EPA Mileage Estimates[3] / Fuel Electric-Only Miles-Per-Gallon of Gasoline-Equivalent (MPGe, Combined)	72.8 62.4 / 62.7 3799 56/44
Height (in) Width (in) Track (in, front/rear) Curb Weight (lbs, 6MT/CVT) Weight Distribution (%, front/rear) EPA Mileage Estimates [3] / Fuel	72.8 62.4 / 62.7 3799 56/44 ACCORD PLUG-IN 115
Height (in) Width (in) Track (in, front/rear) Curb Weight (lbs, 6MT/CVT) Weight Distribution (%, front/rear) EPA Mileage Estimates[3] / Fuel Electric-Only Miles-Per-Gallon of Gasoline-Equivalent (MPGe, Combined) Gasoline-Only (MPG, City/Highway/Combined)	72.8 62.4 / 62.7 3799 56/44 ACCORD PLUG-IN 115 47 / 46 / 46
Height (in) Width (in) Track (in, front/rear) Curb Weight (lbs, 6MT/CVT) Weight Distribution (%, front/rear) EPA Mileage Estimates[3] / Fuel Electric-Only Miles-Per-Gallon of Gasoline-Equivalent (MPGe, Combined) Gasoline-Only (MPG, City/Highway/Combined) Combined Gas-Electric Driving Range Rating (mi)	72.8 62.4 / 62.7 3799 56/44 ACCORD PLUG-IN 115 47 / 46 / 46 570
Height (in) Width (in) Track (in, front/rear) Curb Weight (lbs, 6MT/CVT) Weight Distribution (%, front/rear) EPA Mileage Estimates[3] / Fuel Electric-Only Miles-Per-Gallon of Gasoline-Equivalent (MPGe, Combined) Gasoline-Only (MPG, City/Highway/Combined) Combined Gas-Electric Driving Range Rating (mi) Maximum EV Mode Driving Range Rating (mi)	72.8 62.4 / 62.7 3799 56/44 ACCORD PLUG-IN 115 47 / 46 / 46 570 13